36306-EnPro® Topcoat YM Zn

General Description	Features
Alkyd resin based, air dry, UV resistant, fast drying topcoat semi gloss paint. This paint is reinforced with special adds to apply DTM.	• Semi Gloss • Corrosion Resistance • UV Resistance • High Coverage Performance • DTM
Recommended For	**Limitation**
• Steel and Iron • Agricultural Equipment • On Vehicle Equipment • Machines • Construction • Heating Technology	• Do not paint when the temperature is within 5 degrees of the dew point and do not apply if rain is expected within 2 hours. • Not recommended of immersion service. • Do not use non-ferrous metals such as Aluminium or galvanized.

Product Information			
Standard Colours	**Technical Data**	Black	
	Vehicle Type	Alkyd Resin	
	Volume Solids		
Certification & Qualification	**Coverage (Per 1 kg)**	10m² (Without loss)	
	Recommended DFT	30µm	
	Dry Time @25° C (77° F) @50% RH	Touch	20 minutes
		Complete	3 hours
Storage Information This product has got 1 year shelf life where dried, cool and no UV exposed.	High humidity and cool temperatures will result in longer dry, recoat and service times.		
Surface Preparation Surfaces to be applied should be cleaned from dirt, oil, dust and old paint residues. Sanding is recommended for this process if media and equipment are available. Sandblasting should be done according to SSPC standards.	**Surface Temperatures for Application**	Min	7.2° C (45° F)
		Max	35° C (75° F)
	Thin With	10103-EnPro® Thinner	
Technical Assistance For more information about this product, please contact with your regional sales account executive or please call general customer sales support -00 90 850 622 62 67- 00 90 850 622 62 68	**Clean Up With**	10104-Cleaning -01-	
	Weight per 1 L		
	Flash Point	28°	
	Gloss	80°	
	Volatile Organic Compounds (VOC)		

Çıvgın Boya Kimya Sanayi A.Ş
İzmir Asfaltı Üzeri Gıda Toptancıları Sitesi 7119. Sokak F Blok 20430 Merkezefendi/Denizli/Turkey
00 90 850 622 62 67 – 00 90 850 622 62 68
info@civginboya.com